

Multi Foot MULTIF



Description

The Lindab Multi Foot is designed to be a multi-purpose ductwork, cable and pipework support. The Multi Foot is an extremely versatile and cost effective one piece support available in two sizes with optional antivibration mats. When used with Lindab's Support Channel and Threaded Rod (not included) the Multi Foot provides a complete support solution for a host of applications from cable trays to ductwork

Designed to

- 41 × 41 mm channel
- 40 mm wide channel (horizontally)
- 12 mm threaded (vertically)

Dim	Length mm	Width mm	Height mm	Weight kg	Max Load kg
400	400	180	95	1,7	77
600	600	220	95	2,8	142

Max recommended load is based on each foot producing a loading of 10,0 kN/m², if conditions allow, the maximum load per foot is 500 kg.

Construction

The Lindab Multi Foot plastic mounting feet are manufactured from Polypropylene 20% Glass fibre filled.

Application

Suitable for internal or external applications in temperatures between -30°C to +80°C.

Ordering example

Product	MULTIF	400
Dimension		

Anti Vibration Mat MFAV



Optional

Multi Foot Antivibration Mat 400 MFAV
Multi Foot Antivibration Mat 600 MFAV

Dim	Length mm	Weight kg
400	180	2,5
600	220	4,5

Construction

The antivibration mats are manufactured from Styrene Butadiene Rubber (SBR).

Application

Suitable for internal or external applications in temperatures between -30°C to +80°C.

Ordering example

Product	MFAV	400
Dimension		